

---

CORE C++  
LIGHTNING STORM

## INTERESTING ALGORITHMS (JUST SAY NO TO RAW LOOPS)

Shimon Shore

Chief Architect, Open Source Program

Israel Ministry of Science and Technology

Israel Ministry of Culture and Sport

BASED ON:

BETTER CODE (C++ SEASONING)

SEAN PARENT | PRINCIPAL SCIENTIST


# No Raw Loops

## WHAT IS A RAW LOOP?


- A *raw loop* is any loop inside a function where the function serves purpose larger than the algorithm implemented by the loop

# Two Beautiful Examples

# NO RAW LOOPS




# NO RAW LOOPS




`rotate(f, l, p);`

# NO RAW LOOPS



# NO RAW LOOPS



`rotate(p, f, l);`




# NO RAW LOOPS



```
if (p < f) rotate(p, f, l);  
if (l < p) rotate(f, l, p);
```

# NO RAW LOOPS




```
if (p < f) rotate(p, f, l);  
if (l < p) rotate(f, l, p);
```

# NO RAW LOOPS



```
if (p < f) rotate(p, f, l);  
if (l < p) rotate(f, l, p);
```


# NO RAW LOOPS



```
if (p < f) return { p, rotate(p, f, l) };  
if (l < p) return { rotate(f, l, p), p };
```

C++11

# NO RAW LOOPS



```
if (p < f) return { p, rotate(p, f, l) };  
if (l < p) return { rotate(f, l, p), p };  
return { f, l };
```

# NO RAW LOOPS




```
template <typename I> // I models RandomAccessIterator
auto slide(I f, I l, I p) -> pair<I, I>
{
    if (p < f) return { p, rotate(p, f, l) };
    if (l < p) return { rotate(f, l, p), p };
    return { f, l };
}
```

# NO RAW LOOPS




# NO RAW LOOPS





# NO RAW LOOPS

`stable_partition(p, l, s)`




# NO RAW LOOPS



`stable_partition(f, p, not1(s))`

# NO RAW LOOPS




`stable_partition(f, p, not1(s))`  
`stable_partition(p, l, s)`

# NO RAW LOOPS



`stable_partition(f, p, not1(s))`  
`stable_partition(p, l, s)`

# NO RAW LOOPS




```
return { stable_partition(f, p, not1(s)),  
        stable_partition(p, l, s) };
```

# NO RAW LOOPS



```
template <typename I, // I models BidirectionalIterator
         typename S> // S models UnaryPredicate
auto gather(I f, I l, I p, S s) -> pair<I, I>
{
    return { stable_partition(f, p, not1(s)),
            stable_partition(p, l, s) };
}
```

# NO RAW LOOPS



```
template <typename I, // I models BidirectionalIterator
          typename S> // S models UnaryPredicate
auto gather(I f, I l, I p, S s) -> pair<I, I>
{
    return { stable_partition(f, p, not1(s)),
            stable_partition(p, l, s) };
}
```

# NO RAW LOOPS

```
template <typename I, // I models BidirectionalIterator
         typename S> // S models UnaryPredicate
auto gather(I f, I l, I p, S s) -> pair<I, I>
{
    return { stable_partition(f, p, not1(s)),
            stable_partition(p, l, s) };
}
```



**LIVE**



**CORE C++**

# INTERESTING ALGORITHMS

June 28th

SHIMON SHORE | JUST SAY NO TO RAW LOOPS